

AUTOMATIC SHRINK COMBO SYSTEM

MODEL: HDS1721, IC1772, T3417



Model HDSA1721 Combo

Maximize employee productivity with Heat Seal's Automatic Shrink Wrap Packaging System. This automatic packaging system wraps up to 30 packages per minute. Flexible and reliable the automatic packaging machine offers 10 product presets for quick and easy product change.

This reliable Automatic L Bar Sealer and shrink tunnel system provides a quality packaging solution for shrink wrapping and will help lower applied packaging costs.

We now **GUARANTEE** the standard Automatic system in 4 weeks or less! Please contact a Heat Seal Sales rep for more information.

FEATURES

IC-1772 BELTED INFEED CONVEYOR

- Power and Control from HDSA-1721
- Variable Speed
- Low Pressure Belt

HDSA-1721 AUTOMATIC L-SEALER

- PLC with Color HMI Controls
- Wraps up to 30 Packages per Minute, depending on application and package size
- Optional Closing Conveyor

T-3417 SHRINK TUNNEL

- Adjustable Air Flow
- Digital Temperature Controls
- Multiple Conveyor Options

MODEL SPECS

FILM CAPACITY	22" Wide (56 cm)
L BAR SEALING AREA	17" W, 21" L (45 W, 55 L cm)
INSIDE TUNNEL DIMENSIONS	28" L, 21 1/2" W, 8" H (71 L, 55 W, 20 H cm)
TUNNEL CONVEYOR SPEED	LDR: 0-35/70 Feet per Minute; TMB/SWB/SHB: 0-35 Feet per Minute
OVERALL DIMENSIONS	83" L, 38" W, 57" H (211 L, 97 W, 145 H cm)
WORKING HEIGHT	38" (97 cm)
POWER REQUIREMENTS	220 Volts, 38 Amp, Single Phase
WATTAGE	8,000
WEIGHT	800 lbs. (363 kg)

AVAILABLE OPTIONS

- Closing Conveyor
- Stainless Steel Construction
- Indexing Motion Profile With Stop Sensor (Option with Flighted Infeed Conveyors)
- Center Folder CF-740, Maximum Roll Width - 48"
- FIC-1772- 6' Flighted Infeed Conveyor, Variable Speed

