

# HEAVY DUTY AUTOMATIC L BAR SEALER

MODEL: HDSA1721



## FEATURES

### CONTROL PANEL

- Siemens PLC Controlled with Intuitive Touchscreen Controls
- Stores up to 10 Products Setup Recipes
- 220 VAC, Single Phase Power
- Choose Horizontal or Vertical Product Detection

### SEALING AREA

- 17" W x 21" L Seal Area Accepts Packages up to 4 3/4" H
- Industrial Coated Hot Knife Seal Bars with Digital Temperature Controls
- Motorized Seal Height Adjustment
- Closing Conveyor

### OTHER FEATURES

- Tool-less Change Over with Scaled Adjustments Throughout
- Interlocked Safety Guarding



Model HDSA1721

- Includes Easy Load Film Cradle with Power Unwind, Film Perforating Rollers and Static Eliminator
- Rigid Carbon Steel Construction with Durable Polyurethane Painted Finish
- Includes Casters and Leveling Pads
- Designed to Integrate with Heat Seal's IC1572A Belted Infeed Conveyor and T3417 Shrink Tunnel
- One Year Warranty

## MODEL SPECS

<b>FILM CAPACITY</b>	22" Wide (87 cm)
<b>L BAR SEALING AREA</b>	17" W, 21" L (45 W x 55 cm L)
<b>CONVEYOR SPEED</b>	70 ft./min. (21 m./min.)
<b>OVERALL DIMENSIONS</b>	72" L, 38" W, 60" H (183 L, 97 W, 152 cm H)
<b>WORKING HEIGHT</b>	32-36" (81-91 cm)
<b>POWER REQUIREMENTS</b>	220VAC, 8 A Single Phase, 50/60 HZ
<b>AIR</b>	2 CFM @ 80 PSI
<b>WEIGHT</b>	1020 lbs.

## AVAILABLE OPTIONS

- Stainless Steel Construction
- IC1572A- 6' Integrated Belted Infeed Conveyor, Variable Speed
- FIC-1772- 6' Flighted Infeed Conveyor, Variable Speed
- Indexing Motion Profile With Stop Sensor (Option with Flighted Infeed Conveyors)
- T3417/8LDR - 17" W x 8" H Chamber Opening, 220V 1 phase

