

HEAVY DUTY L BAR SEALER



Specification Sheet

MODEL: HDX2030

FEATURES

CONTROL PANEL

- Conveniently Positioned, **RS-5 Plus** Digital Controller with Three Year Warranty on Original Machine Controller
- Meets UL 508A Standard
- Single Plug 115V power supply
- Cycle Counter Comes Standard with Reset

SEALING AREA

- Hot Knife Exact Seal System with Multiple Profile Options
- Heavy Duty Cast Aluminum Seal Head with Stainless Film Clamps
- Balanced Magnetic Hold Down for Strong, Consistent Seals
- FDA Approved Self Tracking, Polyurethane, Sealing Conveyor with 4" Adjustable Height

OTHER FEATURES

- Two Year Warranty
- Console Unit, Storage Cabinet, Heavy Duty Adjustable Levelers & Casters



- Individually Adjustable Perforating Wheels
- Auto Tensioning Film Cradle
- Stainless Steel Product Loading Tray

MODEL SPECS

FILM CAPACITY	25" Wide (63 cm)
L BAR SEALING AREA	21" W, 30" L
OVERALL DIMENSIONS	65" L, 37" W, 57"H (165 L, 93W, 144H cm)
WORKING HEIGHT	36" (91 cm)
POWER REQUIREMENTS	115 Volts, 15 Amp
WEIGHT	625 lbs. (283 kg)

AVAILABLE OPTIONS

- Stainless Steel Construction
- Electrical Wiring 220 Volt
- Left Hand Reverse Flow
- Air Actuated Sealing Head
- Powered Film Unwind with Perforating Roller and 10 Inch High Adjustable Inverting Head
- Stand Alone Power Scrap Wind-Up
- Spare Parts Kit

Revised 2021

4922 E. 49th Street, Suite 100, Cleveland, OH 44125
www.HeatSealCo.com

Phone: (216) 341-2022 Fax: (216) 341-2163
CustServ@HeatSealCo.com

