

# SHRINK TUNNEL

MODEL: T4832



## FEATURES

### TUNNEL CHAMBER

- Digital Tunnel Temperature Control
- High Velocity Air Flow with Dual Mechanical Controls
- Open Coil Heating Element
- Three Heat Zones
- High Temperature Limit Switch
- Automatic Cool Down Extends Heating Element Life



Model T4832

### CONVEYOR FEATURES

- Quick Change 5/8" Diameter Live/Dead Rollers with 2" Spacing
- One Quarter Horsepower Motor With Adjustable Conveyor Speeds Of Up To 70 Feet Per Minute

### OTHER FEATURES

- Heavy Gauge Adjustable Height Console With Levelers And 3" Casters
- Stainless Steel Model Available
- Two Year Warranty

## MODEL SPECS

<b>INSIDE TUNNEL DIMENSIONS</b>	48" L, 32" W, 12" H (122 cm L, 81 cm W, 30 cm H)
<b>CONVEYOR</b>	Variable Speed, Quick Change Live/Dead Silicone Covered Rollers with 2" Spacing
<b>CONVEYOR SPEED</b>	0 - 35 ft./min. (10.7 m./min.) 0 - 70 ft./min. LDR (0 - 21 m./min. LDR)
<b>OVERALL DIMENSIONS</b>	74" L, 41" W, 58" H (189 cm L, 104 cm W, 148 cm H)
<b>POWER REQUIREMENTS</b>	208~240 Volts, 54 Amps Three Phase
<b>WATTAGE</b>	12,900 Watts
<b>WEIGHT</b>	860 lbs. (391 kg)

## AVAILABLE OPTIONS

- Stainless Steel Construction (T4832S)
- Stainless Steel Wire Mesh Belt Conveyor
- Non-stick Mesh Belt Conveyor
- Roller Spacing: 1"
- Roller Spacing: 1 1/2"
- Pack Cooler Fan (For Polyethylene)
- 16" High Tunnel Opening
- Left Hand Reverse Flow

