

STANDARD DUTY COMBO SHRINK SYSTEM

MODEL: HSE100



FEATURES

CONTROL PANEL

- Express Control Panel for Machine Operations
- Single Plug 115V Power Supply

SEALING AREA

- Impulse Wire Seal System
- Large 16" W by 20" L Seal Area
- Standard Seal Head with Film Clamps
- Adjustable Height Sealing Platform
- Balanced Magnetic Hold Down
- Pre-Wired Seal Conveyor Ready

SHRINK TUNNEL

- Independent Tunnel Temperature Control
- Non-Stick Mesh Tunnel Belt
- Automatic Cool Down Extends Heating Element Life



Model HSE100 shown Fully Loaded

Model HSE100 base machine

OTHER FEATURES

- One Year Warranty
- Four Individually Adjustable Perforating Wheels
- Adjustable Film Cradle

MODEL SPECS

| | |
|---------------------------------|---|
| FILM CAPACITY | 20" Wide (50 cm) |
| L BAR SEALING AREA | 16" W, 20" L (41 W, 51 L cm) |
| INSIDE TUNNEL DIMENSIONS | 20" L, 14" W, 6.5" H (51 L, 36 W, 17 H cm) |
| TUNNEL CONVEYOR SPEED | 0-20 Feet per Minute (0-6 meters per minute) |
| OVERALL DIMENSIONS | 76.5" L, 24" W, 32"/55" H (Table Top/Leg Kit) (195 L, 61 W, 82 H cm) |
| WORKING HEIGHT | 36" (92 cm) - with Leg Kit |
| POWER REQUIREMENTS | 115 Volts, Single Phase, 20 Amp |
| WEIGHT | 380 LBS |
| TUNNEL WATTAGE | 2,000 |

AVAILABLE OPTIONS

- Leg Kit
- Silicone Sealing Conveyor
- Heated Hole Punch

