


ON DEMAND SEAL PLATE SIGNIFICANTLY REDUCES ENERGY CONSUMPTION

FEATURES

- NEW FILM CRADLE MOUNT: Saves Labor, Film Changeover is Fast and Easy with New Design; No Initial Set up or Assembly
- Fixed Distance Photoeye to Detect All Tray Colors
- Electronic Temperature Controlled Film Cut Off Rod
- Two Color LED for Photoeye Indication is Amber to Convey Seal Plate Heating, and Red when Seal Plate Reaches Sealing Temperature
- NEW Circuit Breakers Replace Fuses for Fast and Easy Reset with Less Maintenance
- On-Demand Timer Controlled Heated Seal Plate That Significantly Reduces Power Consumption by 80%
- Seal Plate Reaches Seal Temperature Within Seconds
- Thermistor Controlled Circuit that Reduces Power Consumption as Residual Heat Increases in Seal Plate
- GFCI for Improved Circuit Integrity and Protection
- Stainless Steel Front Plate for Easy Wipe Down
- Rigid Aluminum And Stainless Steel Construction
- Stainless Steel Wrapping Surface
- 13" Maximum Roll Width, 9" Maximum Roll Diameter
- Supplied With A Replaceable Non-Stick Cover to Maintain A Hygienic Seal Surface
- Local Utility Rebates may be Available



MODEL SPECS

MODEL		700ES
FILM MOUNT		NEW Cradle System
FILM CAPACITY		13"
SEAL PLATE		6" x 15"
OVERALL DIMENSIONS		23.36" D, 13" W, 5" H (59 D, 33 W, 13 H cm)
ELECTRICAL SPECIFICATIONS		115 Volt, 60Hz, 132 Watts
WEIGHT		23 lbs. (13kg)
OTHER FEATURES		No Assembly Required, Quick Film Changeover
COMPARABLE TO		625A Mini

