

						₽	3] -
6	2# 2004.000						
6 5	3ft 1	2201-002 1845-029		TUBING, SHRINK, .375 ID (1 IN.) MOTOR PLUG, 90VDC			
4	3ft	2205-002		SLEEVING, BLACK, #3, .234 ID (31 LG.)			
3	6ft	1890-044		WIRE, LT. BLUE, 14 AWG, THWN/MTW (19.5 IN.)			ł
2	2	1878-021		CONNECTOR, BUTT, NON-INSUL, 16/14			•
1	1	1839-015 G		GEAR	GEARMOTOR, 90VDC, 50 RPM		
TEM	QT	PARINU		toric	DESCRIPTION		
Material Specification HEAT SEAL/AMPAK CLEVELAND, OHIO 44125							
AND (IT IS (, AND	UNLESS OTHERWISE SPECIFIED: 9/2/2/ ALL DIMENSIONS IN INCHES MADI			Y:	MOTOR ASSY, PTA CONVEYOR, 1/32 HP		
OR IN ANY CLOSED PLICIT ER AND QUEST.	TOLERANCES: 0.00: ±.010 0.000: ±.005		CHECKED: CHECKED B	SY:	5806-953	(ISION: 0	
		.E: ±1 [.]	<u> </u>		size: B scale: NONE sheet: 1 Of	F: 1	