HEAVY DUTY COMBO SHRINK SYSTEM

MODEL: HDX350



Specification Sheet

FEATURES

CONTROL PANEL

- Conveniently Positioned, **RS-5 Plus** Digital Controller
- Meets UL 508A Standard
- Simple Operation and Precise Temperature Controls
- Cycle Counter Comes Standard with Reset
- Single Cord 220V Single Phase Power Supply

SEALING AREA

- Hot Knife Exact Seal System with Multiple Profile Options
- Large 21" W by 25" L Seal Area
- Heavy Duty Cast Aluminum Seal Head with Stainless Film Clamps
- Balanced Magnetic Hold Down for Strong, Consistent Seals
- Seal Conveyor with Smooth Product Transfer from Seal Area to Tunnel

SHRINK TUNNEL

- Non-Stick Mesh Tunnel Belt with Adjustable Riser Bar for Improved Bottom Shrink
- 12"H Tunnel Opening
- Efficient MaxAir Tunnel Triples the Airflow and Evenly Wraps Air Around Package
- Automatic Cool Down Extends Heating Element Life



HDX350

OTHER FEATURES

- Package Centering System for Even Shrink Sealing and Tunnel Conveyor Move in Tandem Vertically. Also, Includes Tunnel Horizontal Quick Slide Adjustment.
- Two Year Warranty
- Four Individually Adjustable Perforating Wheels
- · Auto Tensioning Film Cradle
- · Heavy Duty Casters and Levelers

R HS Denotes RapidHS 5 Day Program Options

MODEL SPECS

FILM CAPACITY	25" Wide (64 cm)
L BAR SEALING	21" W, 25" L
AREA	(53 W, 64 L cm)
INSIDE TUNNEL	27" L, 20" W, 12" H
DIMENSIONS	(69 L, 51 W, 30.5 H cm)
TUNNEL CONVEYOR	0-20 Feet per Minute
SPEED	(0-6 meters per minute)
OVERALL	95" L, 35" W, 63" H
DIMENSIONS (241 L, 89 W, 150 H cm)	
WORKING HEIGHT	38" (97 cm)
POWER	220 Volts, 48 Amp,
REQUIREMENTS	Single Phase
TUNNEL WATTAGE	6,200
WEIGHT	1080 lbs. (490 kg)

AVAILABLE OPTIONS

- Fully Stainless Steel Construction
- Reverse Flow
- Powered Conveyor Lift
- · Air Actuated Sealing Head
- Added Heated Hole Punch
- Tunnel Belt Options: Stainless Steel Wire Mesh or PTFE Non-Stick Mesh Belt
- Spare Parts Kit (5820-020) **R** HS
- Powered Film Unwind with Perforating Roller and 10 Inch High Adjustable Inverting Head
- GTC180/22- 180 Degree Gravity Turn Around Conveyor
- GTC90/22- 90 Degree Gravity Turn Around Conveyor
- AT36- 36" Rotary Accumulator Table
- AT48- 48" Rotary Accumulator Table



Revised 2019

HEAVY DUTY COMBO SHRINK SYSTEM

HEAT SEAL

Specification Sheet

MODEL: HDX350

MACHINE FOOTPRINT

LENGTH (L)	95"
WIDTH (W)	35" Tunnel Retracted 43" Tunnel Pulled Out
HEIGHT (H)	63" Tunnel Lowers 4"





