

# SHRINK TUNNEL

MODEL: T2615



## FEATURES

### TUNNEL CHAMBER

- Digital Tunnel Temperature Control
- High Velocity Air Flow with Dual Mechanical Controls
- Single Heat Zone
- High Temperature Limit Switch
- Automatic Cool Down Extends Heating Element Life



### CONVEYOR FEATURES

- 1/2" Diameter Live/Dead Rollers with 2" Spacing
- 1/8 Horsepower Motor With Adjustable Conveyor Speeds Of Up To 70 Feet Per Minute

### OTHER FEATURES

- Heavy Gauge Adjustable Height Console With Levelers And 3" Casters
- Stainless Steel Model Available
- Two Year Warranty

## MODEL SPECS

<b>INSIDE TUNNEL DIMENSIONS</b>	26" L, 15" W, 8" H (66 cm L, 38 cm W, 20 cm H)
<b>CONVEYOR</b>	Variable Speed, Live/Dead Silicone Covered Rollers with 2" Spacing
<b>CONVEYOR SPEED</b>	0 - 30 ft./min. (9 m./min.) 0 - 70 ft./min. LDR (0 - 21 m./min. LDR)
<b>OVERALL DIMENSIONS</b>	41" L, 24" W, 52" H (104 cm L, 61 cm W, 132 cm H)
<b>POWER REQUIREMENTS</b>	208~240 Volts, 25 Amps Single Phase
<b>WATTAGE</b>	4,000 Watts
<b>WEIGHT</b>	420 lbs. (191 kg)

## AVAILABLE OPTIONS

- Stainless Steel Construction (T2615S)
- Stainless Steel Wire Mesh Belt Conveyor
- Non-stick Mesh Belt Conveyor
- Non-stick Mesh Belt Overlay (for Live/Dead Roller Conveyor)
- Roller Spacing: 1"
- Reverse Flow

