

SHRINK TUNNEL

MODEL: T4822



FEATURES

TUNNEL CHAMBER

- Digital Tunnel Temperature Control
- High Velocity Air Flow with Dual Mechanical Controls
- Three Heat Zones
- High Temperature Limit Switch
- Automatic Cool Down Extends Heating Element Life

CONVEYOR FEATURES

- 1/2" Diameter Live/Dead Rollers with 2" Spacing
- One Quarter Horsepower Motor With Adjustable Conveyor Speeds Of Up To 70 Feet Per Minute



Model T4822

OTHER FEATURES

- Heavy Gauge Adjustable Height Console With Levelers And 3" Casters
- Stainless Steel Model Available
- Two Year Warranty

MODEL SPECS

INSIDE TUNNEL DIMENSIONS	48" L, 22" W, 8" H (122 cm L, 56 cm W, 20 cm H)
CONVEYOR	Variable Speed, Quick Change Live/Dead Silicone Covered Rollers with 2" Spacing
CONVEYOR SPEED	0 - 30 ft./min. (9 m./min.) 0 - 70 ft./min. LDR (0 - 21 m./min. LDR)
OVERALL DIMENSIONS	74" L, 31" W, 58" H (189 cm L, 79 cm W, 148 cm H)
POWER REQUIREMENTS	208~240 Volts, 65 Amps Three Phase
WATTAGE	18,000 Watts
WEIGHT	675 lbs. (307 kg)

AVAILABLE OPTIONS

- Stainless Steel Construction (T4822S)
- Stainless Steel Wire Mesh Belt Conveyor
- Non-stick Mesh Belt Conveyor
- Non-stick Mesh Belt Overlay (for Live/Dead Roller Conveyor)
- Roller Spacing: 1"
- 12" High Tunnel Opening
- Reverse Flow

