

COMPACT SHRINK TUNNEL

MODEL: T2016



FEATURES

TUNNEL CHAMBER

- 6.5" H by 15" W Tunnel Opening
- Single Chamber Design
- Analog Tunnel Temperature Control
- Automatic Cool Down Extends Heating Element Life
- Built in High Temperature Limit Switch

CONVEYOR FEATURES

- Variable Speed, Non-Stick Mesh Tunnel Belt
- Conveyor Speeds up to 25 FPM

OTHER FEATURES

- Heavy Gauge Steel Construction
- Two Year Warranty

Model T2016



MODEL SPECS

INSIDE TUNNEL DIMENSIONS	20" L, 15" W, 6.5" H (51 cm L, 38 cm W, 16.5 cm H)
CONVEYOR	Variable Speed, Non-Stick Mesh Belt
CONVEYOR SPEED	0-25 FPM (0-7.6 meters per minute)
OVERALL DIMENSIONS	40" L, 20" W, 48" H (102 cm L, 51 cm W, 122 cm H)
POWER REQUIREMENTS	115 Volts, 20 Amp, Single Phase
WATTAGE	2,000 Watts
WEIGHT	172 lbs. (78 kg)

AVAILABLE OPTIONS

- Stainless Steel Model Available
- Painted Console Leg Kit with 3" Casters
- Stainless Console Leg Kit with 3" Casters

