

All Electric Automatic Side Sealer

MODEL: HDX 3000



FEATURES

- All Electric, No Air Required
- Interlocked Acrylic Guard Door w/ easy machine access
- Schneider Electric PLC Touchscreen Controls
- Brushless Servo Motor Controlled Hot Knife Seal System
- Brushless Servo Motor Controlled Side Seal
- Motorized Adjustment of Inverting Head and Seal Height
- Swing Arm Control panel
- Plug and Play Set Up
- 20-100 Feet/Min Conveyor Speeds, Variable Frequency AC Drive



OTHER FEATURES

- Motorized Movement of
 - Seal Opening
 - Seal Height
 - Inverting Triangle Height
- Adjustable Seal Force
- Closing Conveyor
- Seal Cooling for Polyethylene
- Extended Infeed and Outfeed Belts
- Powder Coated Steel Construction
- FDA Approved Belts
- Two Individually Adjustable Film Perforators
- Easy Thread Scrap Rewind w/ Scrap Break And Scrap Film Alarms
- Illuminated Work Area
- Casters and Leveling Pads
- One Year Limited Warranty
- Simple Recipe Storage

MODEL SPECS

SEAL AREA	15.5" W, ∞" L (400mm W, 600mm L)
FILM CAPACITY	27.5" W, 11.75"OD (700mm W, 300mm OD)
CONVEYOR SPEED	VARIABLE 20 – 100 FPM (6-30 mpm)
PRODUCTION RATE	0 – 40 PPM, Dependent upon product and film size
MAXIMUM PRODUCT DIMENSION	∞" L, 15.5" W, 9.25" H (∞" L, 400mmW, 240mmH) Maximum dimensions cannot be used simultaneously
POWER REQUIREMENTS	208-240 VAC, SINGLE PHASE, 13A
CONVEYOR HEIGHT	34.8" (880mm)
OVERALL DIMENSIONS	88" L, 95" W, 77" H (2244mm L, 2395mm W, 1950mm H)
WEIGHT	1940 Lbs. (880) Kg)

AVAILABLE ACCESSORY OPTIONS

- Infeed and Outfeed Conveyors
- Printer
- Photocell Kit for Printed Film
- Electric Film Hole Punch
- Irregular Shape Product Photo Cell Kit (5pc)
- Product Guides for Unstable Products

